

MILBOOK



Windows



Android



IP65



GPS



Dual-battery



Bluetooth



Camera



1D



2D



NFC



4G



WiFi



Fingerprint



Dystrybucja i serwis:
AP-FLYER Sp. z o.o., ul. Żegańska 2d, 04-713 Warszawa
Tel: +48 22 613 0487, Fax: +48 22 613 0612
www.ap-flyer.pl e-mail: info@ap-flyer.pl



Basic parameters	MILBOOK R13 Notebook	MILBOOK R14 Notebook	MILBOOK R15 Notebook	MILBOOK F10 Tablet	MILBOOK F20 Tablet	MILBOOK A8 Tablet	MILBOOK A16 Tablet
Dimension	322 x 233 x 26mm	356 x 269 x 37mm	397 x 271 x 37mm	290 x 196 x 22mm	331.5 x 230.3 x 22mm	225.6 x 144.6 x 21.5mm	280.4 x 187 x 26.6mm
Weight	2100 g	2850 g	3300 g	1140 g	1500 g	715 g	1014 g
Device Color	black	black	black	black	black	black	black
LCD	13.3 inch FHD IPS 16:9, 1920*1080	14 inch FHD IPS 16:9, 1920*1080	15.6 inch FHD IPS 16:9, 1920*1080	10.1 inch FHD IPS 16:10, 1920*1200	12 inch FHD IPS 16:10, 1920*1200	8 inch IPS 16:10, 800x1280/1200x1920	10.1 inch IPS 16:10, 800x1280/1200x1920
Touch Panel	Optional 10 points Capacitive, G+G, Corning Gorilla Glass	Optional 10 points Capacitive, G+G, Corning Gorilla Glass	-----	10 points Capacitive, G+G	10 points Capacitive, G+G	5 point G+G capacitive touch screen Corning® Gorilla® Glass	10 point G+G capacitive touch screen Corning® Gorilla® Glass
Camera	Front 2.0 MP	Front 2.0 MP	Front 2.0 MP	Front 2.0 MP; Rear 8.0 MP	Front 2.0 MP; Rear 8.0 MP	Front 5.0MP; Rear 13.0MP	Front 5.0MP; Rear 13.0MP
I/O	HDMI x 1, POGO 5pin x 1(Optional), Type C x 1, USB 3.0 x 3, SIM Card x 1, TF Card x 1, DB9 RS232 x 1, RJ45 x 1, Φ3.5mm standard earphone jack x 1, DC 19V 3.42A x 1	HDMI x 1, POGO 5pin x 1, USB 2.0 x 1, USB 3.0 x 3, SIM Card x 1, SD Card x 1, DB9 RS232 x 1, RJ45 x 2, Φ3.5mm standard earphone jack x 1, DC 19V 3.42A x 1	HDMI x 1, POGO 5pin x 1, USB 2.0 x 1, USB 3.0 x 3, SIM Card x 1, SD Card x 1, DB9 RS232 x 1, RJ45 x 2, Φ3.5mm standard earphone jack x 1, DC 19V 3.42A x 1	USB 3.0 x 1, Type C x 1, SIM Card x 1, TF Card x 1, HDMI 1.4a x 1, DB9 RS232 x 1, RJ45 x 2, 12pins Pogo Pin x 1, Φ3.5mm standard earphone jack x 1, Φ5.5mm DC jack x 1	USB 3.0 x 1, Type C x 1, SIM Card x 1, TF Card x 1, HDMI 1.4a x 1, 12pins Pogo Pin x 1, Φ3.5mm standard earphone jack x 1, Φ5.5mm DC jack x 1	HDMI 1.4a x 1, USB 3.0 Type-A x 1, USB Type-C x 1, SIM Card x 1, TF Card x 1, 12pins Pogo Pin x 1, Φ 3.5mm standard earphone jack x 1, Φ 3.5mm DC jack x 1	HDMI 1.4a x 1, USB 3.0 Type-A x 1, USB Type-C x 1, SIM Card x 1, TF Card x 1, 12pins Pogo Pin x 1, DB9 RS232 x 1, RJ45 x 1, Φ3.5mm standard earphone jack x 1, Φ3.5mm DC jack x 1
Power	AC100V ~ 240V, output DC 19V/3.42A/65W	AC100V ~ 240V, output DC 19V/3.42A/65W	AC100V ~ 240V, output DC 19V/3.42A/65W	AC100V ~ 240V, output DC 19V/3.42A/65W	AC100V ~ 240V, output DC 19V/3.42A/65W	AC100V ~ 240V, 50Hz/60Hz, output DC 5V/3A	AC100V ~ 240V, 50Hz/60Hz, output DC 5V/3A
GPS	Support GPS	Support GPS	Support GPS	Support GPS, Beidou, glonass	GPS, Beidou, glonass	Built-in GPS, glonass	Built-in GPS, glonass
Fingerprint	SPI fingerprint (power on login)	SPI fingerprint (power on login)	SPI fingerprint (power on login)	SPI Fingerprint (windows hellow boot login)	SPI Fingerprint (windows hellow boot login)	-----	Optional, FPC1020
NFC	-----	Optional: NXP NFC 13.56MHz Support ISO/IEC 14443A/14443B/15693/18092/mifare protocol, Card reading distance : 4cm	Optional: NXP NFC 13.56MHz Support ISO/IEC 14443A/14443B/15693/18092/mifare protocol, Card reading distance : 4cm	Optional NXP100	Optional NXP100	Built-in, ISO/IEC 14443A	Built-in, ISO/IEC 14443A
Battery							
Capacity	11.1V/2800mAh x 2	7.4V/6300mAh	7.4V/6300mAh	7.4V/5000mAh	7.4V/6300mAh	3.7V/8500mAh	3.7V/10000mAh
Type	Removable Li-polymer battery	Removable Li-polymer battery	Removable Li-polymer battery	Removable Li-polymer battery	Removable Li-polymer battery	Built in polymer lithium ion battery	Removable Li-polymer battery
Endurance	10 hrs (Default 50% volume, default 200 nit, play 720P HD video)	8.5hrs (Default 50% volume. default 200 nit, play 720P HD video)	8 hrs (Default 50% volume. default 200 nit, play 720P HD video)	5 hrs (50% volume sounds, 200 lumens brightness, 1080P HD video display by default)	5 hrs (50% volume sounds, 200 lumens brightness, 1080P HD video display by default)	8hrs (50% volume sounds, 200 lumens brightness, 1080P HD video display by default)	12hrs(default 50% volume. default 200 nit, play 1080P HD video)
Bridge battery	-----	1750mAh, Li-polymer battery, Endurance 30 mins	1750mAh, Li-polymer battery, Endurance 30 mins	860mAh, Li-polymer battery, Endurance 30 mins	860mAh, Li-polymer battery, Endurance 30 mins	-----	-----
Performance parameter							
CPU	Intel® i5-1135G7	Intel® Core™ i5-8250U/i7-8550U	Intel® Core™ i5-8250U/ i7-8550U	Intel® Core™ i5-8250U/i7-8550U	Intel® Core™ i5-8250U/i7-8550U	Qualcomm (OCTA Core), 2.0GHz	Qualcomm (OCTA Core), 2.0GHz
OS	Windows 10/11	Windows 10/11	Windows 10/11	Windows 10/11	Windows 10/11	Android 10/GMS	Android 10/GMS
RAM	8GB/16GB DDR4L	8GB/16GB DDR4L	8GB/16GB DDR4L	8GB/16GB DDR4L	8GB/16GB DDR4L	4GB	4GB
ROM	256GB/512GB	256GB/512GB	256GB/512GB	128GB/256GB/512GB	128GB/256GB/512GB	64GB	64GB
Network connections							
WIFI	WiFi 802.11 (a/b/d/e/g/h/i/k/n/r/u/v/w/ac/ax)	2.4G+5.8G dual frequency, WIFI 802.11 (a/b/g/n/ac)	2.4G+5.8G dual frequency, WIFI 802.11 (a/b/g/n/ac)	2.4G+5.8G dual frequency, WIFI 802.11 (a/b/g/n/ac)	2.4G+5.8G dual frequency, WIFI 802.11 (a/b/g/n/ac)	2.4G+5G dual frequency, WIFI 802.11 (a/b/g/n/ac)	2.4G+5G dual frequency, WIFI 802.11 (a/b/g/n/ac)
Bluetooth	BT5.1	BT4.2 (BLE) class1 transmission distance: 10m	BT4.2 (BLE) class1 transmission distance: 10m	BT4.2 (BLE) class1 transmission distance: 10m	BT4.2 (BLE) class1 transmission distance: 10m	BT4.1	BT4.1
4G	LTE FDD: B1/B3/B7/B8/B20/B28A, WCDMA: B1/B8, GSM: B3/B8	LTE FDD: B1/B3/B5/B7/B8/B20/B28A, LTE TDD: B40, WCDMA: B1/B2/B5/B8, GSM: B2/B3/B5/B8	LTE FDD: B1/B3/B5/B7/B8/B20/B28A, LTE TDD: B40, WCDMA: B1/B2/B5/B8, GSM: B2/B3/B5/B8	LTE FDD: B1/B3/B7/B8/B20/B28A, WCDMA: B1/B8, GSM: B3/B8	LTE FDD: B1/B3/B7/B8/B20/B28A, WCDMA: B1/B8, GSM: B3/B8	CMCC 4M: LTE B1/B3/B5/B7/B8/B20/B38/B39/B40/B41 WCDMA B1/B2/B5/B8, GSM B2/B3/B5/B8	CMCC 4M : LTE B1/B3/B5/B7/B8/B20/B38/B39/B40/B41 WCDMA B1/B2/B5/B8, GSM B2/B3/B5/B8
Reliability							
Operate Temperature	-20℃ ~ 60℃	-20℃ ~ 60℃	-20℃ ~ 60℃	-20℃ ~ 60℃	-20℃ ~ 60℃	-20℃ ~ 55℃	-20℃ ~ 55℃
Store Temperature	-30℃ ~ 70℃	-30℃ ~ 70℃	-30℃ ~ 70℃	-30℃ ~ 70℃	-30℃ ~ 70℃	-30℃ ~ 70℃	-30℃ ~ 70℃
Humidity	95% Non-Condensing	95% Non-Condensing	95% Non-Condensing	95% Non-Condensing	95% Non-Condensing	95% Non-Condensing	95% Non-Condensing
IP Grade	IP65	IP65	IP65	IP65	IP65	IP67	IP65
Module extension (5 choose 1)							
Ethernet interface	-----	-----	-----	RJ45(10/100M) x 1	RJ45(10/100M) x 1	-----	-----
Serial port	-----	-----	-----	DB9(RS232) x 1	DB9(RS232) x 1	-----	-----
USB 2.0	-----	-----	-----	USB 2.0 x 1	USB 2.0 x 1	-----	-----
1D	-----	-----	-----	MOTO SE655E100R/Optical resolution: 5mil/scan speed: 50 times/s	MOTO SE655E100R/Optical resolution: 5mil/scan speed: 50 times/s	MOTO SE655E100R/Optical resolution: 5mil/scan speed: 50 times/s	MOTO SE655E100R/Optical resolution: 5mil/scan speed: 50 times/s
2D	-----	-----	-----	Honeywell N3680/Optical resolution: 5mil/scan speed: 50 times/s	Honeywell N3680/Optical resolution: 5mil/scan speed: 50 times/s	Zebra SE2707/Optical resolution: 5mil/scan speed: 50 times/s	Honeywell N3680/Optical resolution: 5mil/scan speed: 50 times/s

Application Range

Various modules and accessories can be selected to meet customers' application in various industries.



Outdoor Exploration



Military Equipment



Finance



Animal Husbandry



Agricultural Production



Outdoor Work



Equipment Monitoring



Industrial Manufacture




Power Maintenance



Equipment Testing



Automobile Manufacturing



Public Security



Certified by independent third-parties for MIL-STD-810G as well as ANSI/ISA 12.12.01 and MIL-STD-461G/461F.



Certified by independent third-parties for IP65/IP67 ratings.



Survived drop tests up to 4 feet (122 cm), rigorous vibration and impact protection tests.



Unsurpassed thermal solution for continuous work in mission-critical situations.



Experience peak performance in extreme temperatures, whether in freezing cold up to -30°C or extreme hot temperatures of 60°C.



Designed from the ground up with high-per-formance materials for full protection.



Leading rugged design to increase productivity and efficiency for any conditions.



Dual-battery that allows up to 10 hours of work.

Dystrybucja i serwis:
AP-FLYER Sp. z o.o., ul. Żegańska 2d, 04-713 Warszawa
Tel: +48 22 613 0487, Fax: +48 22 613 0612
www.ap-flyer.pl e-mail: info@ap-flyer.pl