

G24 Temperature Controller



The G24 Temperature Controller

Synventive introduces the next generation in temperature control: the G24. Focused on the plastics industry, Synventive is an expert in process optimization. The G24 is everything you would expect in a next generation control system from Synventive:

- Easier to Use
- Less Expensive
- Smaller
- Faster
- More Flexible/Standardization
- Improved Interlocks
- Mold Doctor®
- Early Material/Plastic Leak Detection
- 5 Year Warranty*

Partnership

Hot runner molding requires a temperature controller. If the temperature controller fails, the process either stops or is crippled. When selecting a temperature control supplier, you are selecting a partner who is critical to your product and profitability.

Triangulated Control Technology®

All Synventive temperature controllers feature Triangulated Control Technology®. Using this unique technology, our controllers:

Sense – Twenty (20) times per second, Synventive controllers precisely measure the temperature.

Control – The proprietary self-optimizing Synventive PID² control algorithm adjusts if the actual temperature deviates 0.03°F (0.014°C) from set point. The second derivative (PID²) monitors the actual temperature rate of change. As a result, the output to the heater is regulated in advance of the typical proportional band to limit or eliminate over and undershoot.

Actuate – Using phase angle fired output (0.1% resolution; 1000 steps), the Synventive controller delivers smooth and exact power to each heater for the ultimate in temperature control.

Triangulating your process with a Synventive controller means achieving better temperature control, which could result in:

- Enhanced part quality
- Reduced scrap
- Improved part weight consistency
- Material savings
- Higher profit margins



Power Priority®


“Low mass”, or extremely small hot runner nozzles are a unique challenge to control. To smooth the power and the melt heat history, Synventive created Power Priority®. Power Priority® smooths the power output to individual zones. Users have the option to manually apply a Power Priority® set point from 1 (light) to 4 (heavy), providing unparalleled control for applications where it is most needed.

Protection

Closed loop wet heater bakeout - 120 times per second (at 60 Hz), the G24 module checks the heater for a short. If the heater is shorted, the output is adjusted within 8.3 milliseconds to protect the heater, cables and controller.

Reliability

Synventive products lead the market in reliability. The expected life is 10 – 15 years based on the quality of heater electrical maintenance. Some Synventive controllers have been in continuous operation for 25+ years.



Easier to Use

Best industry practices and actual operation are often not the same. The G24 is designed to be understood with 5 minutes of training, and programmable to automatically operate according to the industry's best practices. An optional Sequence Start can be activated to only power the manifold/sprue zones, wait until they reach temperature, start a soak period countdown timer and finally heat the smaller, faster heating nozzle zones. This practice is always recommended but seldom done in the industry. The primary benefits include maintaining the integrity of the manifold seal by controlling heat expansion and preventing material degradation caused by excessive nozzle heater material residence time.

Less Expensive

By leveraging the global electronics supply chain with new components that take the place of multiple previous components, Synventive has been able to reduce the price of the G24 product line in relation to existing Synventive products. Synventive, long known as the reliability and control leader in the industry, combines a competitive price with superior performance in the G24 controller.

Smaller

Each control module has a 15 amp per zone output rating. Up to 24 zones can be placed in a single control block. When compared to the Synventive TTC product line, this specific 128 zone controller has a 48% smaller footprint.

Faster

The G24 utilizes industrial USB connectivity for up to a 0.1 second screen update rate. Streaming real-time control numbers to the screen allows the user to better see what is happening inside the tool so they can diagnose difficult to understand issues.

More Flexible/Standardization

The standard two zone 15 amp per zone output module easily controls both nozzle and manifold zones making the controller easy to use across a range of molds for effortless production scheduling. The G24 is even able to control up to 30 amp zones with a 15 amp module by restricting the maximum output to 15 amps using our RMS limiting feature.

Improved Interlocks

The tools of today are far more sophisticated and sensitive than the tools of yesteryear. Machine interlocks ensure bad parts are not produced and catastrophic damage is avoided. The G24 makes the interlocking task easier than ever with on-screen interlock signal inversion and manual testing signals to speed setup.

Mold Doctor®

Automate your mold troubleshooting with Mold Doctor®. Elusive problems that appear suddenly and without changes to the process can be diagnosed with a quantitative thermodynamic zone analysis.

Early Leak Detection

When material/plastic leaks into the mold it occupies a former air space. Eliminating the air space creates a heat sink to the surrounding mass. In automatic mode, the controller increases the power to compensate for the loss in heat. The third generation of the Synventive watt/leak alarm speeds the initial setup and alerts the user when a leak first occurs. Typically, the change in control wattage is 10%. Precisely measuring the actual wattage can be the difference between a short trip to the tool room or weeks of lost production.

5 Year Warranty*

Every G24 controller comes with a full 5-year warranty and is backed by the industry-leading worldwide service and support that our customers expect from Synventive.



128 zones

96 cavity

Delta: 150 amp
Wye: 70 amp

Width: 20in / 50.8cm
Depth: 23in / 58.4cm
Height: 50.25in / 127.6cm



Standard Configurations

Control Blocks

24 zone control block

Each zone rated up to 15 amps

Maximum circuit breaker shown for each enclosure



12 zone control block

Each zone rated up to 15 amps

More heat sink per module for higher amperage applications

Maximum circuit breaker shown for each enclosure

T1

24 zones

Delta: 100 amp

Wye: 50 amp

T1

12 zones

Delta: 150 amp

Wye: 80 amp

T2

48 zones

Delta: 100 amp

Wye: 50 amp

T2

24 zones

Delta: 150 amp

Wye: 80 amp

Custom Configurations

A custom G24 controller can contain a mixture of 12 and 24 zone control blocks. Custom controllers can also have non-standard wiring



S1

24 zones

Delta: 100 amp

Wye: 50 amp



S2

48 zones

Delta: 100 amp

Wye: 50 amp



S2

24 zones

Delta: 150 amp

Wye: 80 amp

Standard Circuit Breakers

Enclosure	30	50	70	80	100	125	150	200	250	300
S or T short top	D or W	D or W	Delta		Delta					
S or T tall top		D or W	Delta	Wye	Delta	Delta	Delta			
D tall top		D or W	D or W		D or W	D or W	D or W	D or W	Delta	Delta



S3
72 zones
Delta: 100 amp
Wye: 50 amp

S3
36 zones
Delta: 150 amp
Wye: 80 amp



D2
96 zones
Delta: 150 amp
Wye: 70 amp

D2
48 zones
Delta: 300 amp
Wye: 200 amp



D3
144 zones
Delta: 150 amp
Wye: 70 amp

D3
72 zones
Delta: 300 amp
Wye: 200 amp



D4
192 zones
Delta: 150 amp
Wye: 70 amp

D4
96 zones
Delta: 300 amp
Wye: 200 amp

Transformers


Transformers

Optional 480 VAC to 240 VAC Delta/Delta three phase 2:1 step down transformers are available. The smaller transformer pod can contain a 15, 30 or 45 kva transformer. The larger transformer pod can contain a 75 or 112 kva transformer. Each transformer pod is detachable, has forced air cooling and an independent circuit breaker.




Standard Enclosure Connectors

S (Separate HBE24 dual latch)




D (Separate HD25 single latch)




Thermocouple Polarity
 (+) on pins A1, A3, A5, A7, B2, B4, B6, C1, C3, C5, C7, A9
 (-) on pins A2, A4, A6, A8, B3, B5, B7, C2, C4, C6, C8, C9

M (Combination HBE48 single latch)




Y (Combination HBE24 single latch)




Thermocouple Polarity
 (+) on pins 3, 7, 11, 15, 19, 23
 (-) on pins 4, 8, 12, 16, 20, 24

E (Combination HBE24 dual latch V1)




F (Combination HBE24 dual latch V2)



Thermocouple Polarity
 (+) on pins 13, 15, 17, 19, 21, 23
 (-) on pins 14, 16, 18, 20, 22, 24

P (Separate HBE48 Single Latch)



Mold Doctor®

Troubleshoot Your Mold

Mold Doctor® is an off-line (tool room), advanced troubleshooting tool consisting of four diagnostic tests:


Wiring Analysis: checks the wiring of the tool. The software clearly tells the user of miswired zones and how to fix them.

Fault Analysis: quickly identifies the following problems: thermocouple open, thermocouple reversed, thermocouple pinched, open fuse, heater short/wet, heater open, uncontrolled output and ground fault.

Thermodynamic Analysis:

automatically heats all selected zones to 400° F (204° C) and cools to 330° F (165° C). During the heating and cooling process Mold Doctor® records critical information and reports to the user. Compare like zones against one another; major differences in the four key areas (resistance, power consumption, heating and cooling rates) will point you towards a solution. Once the tool is qualified, save a thermodynamic analysis as your known “good parts” baseline. Future problems will be easy to diagnose using the historical mold performance tool.

Historical Mold Performance: allows the user to easily compare a known “good” thermodynamic analysis baseline to the current “suspect” thermodynamic analysis. Intuitively troubleshoot your mold with hard data.



Calibration

Calibrate your controllers in house quickly, easily and without a calibration technician. Establish a thermocouple source equivalent to the controller. The difference between the calibrator value and the control screen is the calibration error. The Calibration software corrects the error with an accuracy of ± 0.2° F (± 0.1° C).

Faster (0.1 sec Screen Updates)

Chart Recording


Chart recorder and statistical analysis software allows the user to record the performance of their hot runner tool, print reports to the USB drive or watch databases of production runs on-screen with our playback mode. Pause live action on the line graph and manually or automatically place injection marks on the screen for in-depth analysis.



Cavity Map Pro™

Cavity Map Pro™


Quickly create a cavity map that is saved with the mold design. The on-screen tools allow the user to create common nozzle layout patterns instantly. Select zones to study closer and flip the image to quickly identify which zone/cavity to change or investigate.



“Lights Out” Molding

Improved Interlocks


The tools of today are far more sophisticated and sensitive than the tools of yesteryear. Machine interlocks ensure bad parts are not produced and catastrophic damage is avoided. The G24 makes the interlocking task easier than ever with on-screen interlock signal inversion and manual testing signals to speed setup.



Best Practices

























Power Application

An optional Sequence Start can be activated to only power the manifold/sprue zones, wait until they reach temperature, start a soak period countdown timer and finally heat the smaller, faster heating nozzle zones. This practice is always recommended but seldom done in the industry. The primary benefits include maintaining the integrity of the manifold seal by controlling heat expansion and preventing material degradation caused by excessive nozzle heater material residence time. When the “Must use sequence start to turn zones on” button is selected all other methods of applying power are disabled to guarantee proper startup.



Detailed Controller Comparison

	LEC	TTC	G24
Core Description			
Temperature control	■	■	■
Temperature control - maximum zones	*24+	640	480
Sequential valve gate control - integrated option		■	
Sequential valve gate control - maximum zones		32	
5 year warranty (2 years on touch screen interface)	■	■	■
Modular design	■	■	■
Controller warm up time - instant	■	■	■
If interface fails – the controller still controls	■	■	■
Emergency interface - use a Windows® computer	XP	XP	XP or 7
Automatic/manual control	■	■	■
Zone “on”, “off” and “locked off”	■	■	■
Set points in tenths		■	■
Adaptive PID ² control algorithm with Power Priority®	■	■	■
Algorithm is executed 20 times per second	■	■	■
Extended tuning ranges (fast/slow)	■	■	■
Output resolution 0.1%	■	■	■
Output attenuation - maximum output (1% increments)			■
RMS limit to module max. - control larger heaters (30a max.)			■
Phase angle firing (1000 Steps; 0.1%)	■	■	■
Wet heater bakeout	■	■	■
Power compensation in manual mode	■	■	■
Degree F/C	■	■	■
Thermocouple J/K	■	■	■
Thermocouple (T/C) filtering - none	■	■	■
T/C resolution 0.03° F (0.014° C) over full scale	■	■	■
T/C calibration accuracy 0.2° F (0.1° C) over full scale	■	■	■
Operating temperature 32-122° F (0-50° C)	■	■	■
Input power 180-265 VAC; 480 VAC optional	■	■	■
Delta/wye convertible option	■	■	■
Circuit breaker sized to load - TTC/G24 - 300 amp maximum	■	■	■
Actual Values			
Actual temperature	■	■	■
% Output	■	■	■
Deviation from set point		■	■
Amps (resolution 0.01 amps)	■	■	■
Volts		■	■
Watts		■	■
Kilowatt monitor (instant, average, max., min.)			■
Ohms		■	■
Alarms			
(+) High temperature (adjustable; 20° F [10° C] default)	■	■	■
(-) Low temperature (adjustable; 20° F [10° C] default)	■	■	■
Thermocouple open (remembered % output)	■	■	■
Thermocouple reversed	■	■	■
Thermocouple pinched (adjustable time)	■	■	■
Open fuse	■	■	■
Shorted heater/wet	■	■	■
Programmable heater short threshold (amps)			■
Open heater	■	■	■
Uncontrolled output (relay power cut off)	■	■	■
Heater resistance monitoring (predict failure)		■	■
Heater wattage monitoring (detect leaks) - auto calc.		■	■
Ground fault detection			■
Critical over temperature alarm (adjustable)	■	■	■
Temperature monitoring (J/K) with programmable action		■	■
Alarm history - zone alarms		■	■
Alarm history graph - zone alarms			■
Zone alarm configure - “none”, “flasher”, “flasher & contacts”			■
Alarm history - system and status			■

	LEC	TTC	G24
Operational Features			
Menu storage		1000+	1000+
Menu "auto save" (optional)			
Programmable groups		■	■
Instant grouping		■	■
Sequence Start (up to 4 stages with delay timers)		■	■
Sequence Cool (up to 4 stages with delay timers)		■	■
Sequenced Power Up - manual activation		■	■
Boost (selectable time/amount) - Automatic mode	■	■	■
Boost (selectable time/amount) - Manual mode			■
Trim		■	■
Even Heat (enable/disable - 20° F [10° C] max. variance)	■	■	■
Even Cool (controlled cooling - 15° F [7° C] max. variance)		■	■
Automatic set point limit	■	■	■
Manual set point limit	■	■	■
Security levels	■	■	■
Security level customization (4 levels)			■
On power up "on" or "off" ("ask" touch screen only)	■	■	■
Auto load manual remembered % output		■	■
Operator identification		■	■
Tool graphics with real time data overlay		■	■
Cavity Map Pro™ with "mirror" button			■
Thermocouple "rewire"		■	■
Copy Output		■	■
Standby timer until system "off"		■	■
PDF viewer - import or export files		■	■
USB port		■	■
On-line help		■	■
Software Features			
Maximum screen update rate (in seconds)	6	0.5	0.1
E-Z Screen - 5 minutes to train			■
Chart Recording (SPC data/graphing)		■	■
Pause line graph with "injection marks" (manual and automatic)			■
Instant data reporting (hours)	 / 24	24	48
Data report storage (up to 1 year) - pdf format		■	■
Mold Doctor® (advanced troubleshooting)		■	■
Calibration (0.2° F [0.1° C] accuracy over full scale)		■	■
On screen printing		■	■
Print to USB drive			■
Networking (Ethernet IP) - stream .csv file - bidirectional		■	■
Remote troubleshooting/operation		■	■
Time and date change during operation			■
Touch screen calibration during operation			■
On-screen keyboard for Windows® tasks			■
Cable Connections			
Enclosure connectors - seven standard choices	■	■	■
Custom control enclosure connectors		■	■
Custom tool end of cable connectors	■	■	■
Software identification of enclosure connectors and pins			■
Inputs (24 VDC required)			
Standby (voltage to activate) (also manually activated)	■	■	■
Standby (no voltage to activate)			■
Control inhibit (voltage to activate)	■	■	■
Control allow (voltage to activate)	■	■	■
Material protection		■	■
Sequenced power up		■	■
Even Cool remote activation			■
Remote boost		■	■
Cycle Start - automatic input for line graph			■
Mold ID - 63 combinations - auto menu load		■	■
Outputs			
Resettable alarm output		■	■
Non-resettable alarm output	■	■	■
"OK to Run" output with status page		■	■
Audible alarm		■	■
Manual activation/deactivation to speed interlock setup			■
Miscellaneous			
Find this module LED		■	■
Daisy chain enclosures	■	■	■



– LEC touch screen or laptop required

* LEC touch screen able to manage 24+ zones with Synventive assistance

Windows XP® and Windows 7® are registered trademarks of Microsoft Corporation

Performance

Thermocouple Calibration Accuracy	0.2°F (0.1°C)
Control Accuracy (steady state)	± 0.1°F (± 0.05°C)
Heater Short Detection Time	8.3 msec. or 120 times per second at 60 Hz
PID ² Algorithm Execution Time	50 msec. or 20 times per second
Tuning	Automatic, self optimizing, manual override
Manual Mode	Power compensation for incoming voltage variation
Degrees F or C	Field Selectable
Operating Range	0-932°F (0-500°C)
Output Range	0-240 VAC, Phase angle fired, 1000 steps
Standby Temperature	User Selectable (0-932°F, 0-500°C)
Remote Input	24 VDC

Input

Thermocouple	Type J standard; Type K selectable
Cold Junction Compensation	Internal to enclosure
External Resistance	10 Meg. Ohms
Temp. Variation due to T/C Length	None

Electrical

Input Voltage	180-265 VAC Delta/Wye (phase voltage)
Frequency	47-53 Hz, 57-63 Hz
Ambient Temperature Range	32-122°F (0-50°C)
Humidity Range	10-95% non-condensing
Output Module Rating	240 VAC; 2 zone - 15 amps/zone 3600 watts/zone
Communications Electrical Standard	Industrial USB 2.0

Performance Standards

U.S., Canadian and International: *Designed to meet	CE Mark; EMC: IEC 61000 - (6-2, 6-4, 4-2, 4-3, 4-4, 4-5, 4-6, 4-11) Safety* IEC 61010, UL-508, UL-873 and CSA
--	--

Physical

	*Height (inches/millimeters)	Width (inches/millimeters)	Depth (inches/millimeters)	*Weight (pounds/kilograms)
T1 enclosure - short top	21.25/540	10/254	23/584	75.1/34.1
T1 enclosure - tall top	25.75/654	10/254	23/584	80.1/36.3
T2 enclosure - short top	32.00/813	10/254	23/584	130.4/59.1
T2 enclosure - tall top	36.50/927	10/254	23/584	135.4/61.4
S1/S2 enclosure - short top	35.00/889	20/508	23/584	139.4/63.2
S1/S2 enclosure - tall top	39.50/1003	20/508	23/584	144.4/65.5
S3 enclosure - tall top	50.25/1276	20/508	23/584	199.7/90.6
D2 enclosure - tall top	39.50/1003	20/508	23/584	243.6/110.5
D3 enclosure - tall top	50.25/1276	20/508	23/584	343.2/155.7
D4 enclosure - tall top	61.00/1549	20/508	23/584	442.8/200.9

*Height and weight excludes screen
Specifications subject to change without notice



North America

Synventive Molding Solutions Inc.
10 Centennial Drive
Peabody, MA 01960, USA
Tel.: +1 978 750 8065
Fax: +1 978 646 3600
E-Mail: info@synventive.com

Europe

Synventive Molding Solutions GmbH
Heimrodstr. 10
64625 Bensheim, Germany
Tel.: +49 (0) 6251 / 9332-0
Fax: +49 (0) 6251 / 9332-90
E-Mail: infohrde@synventive.com

Asia

Synventive Molding Solutions (Suzhou) Co.Ltd.
12B Gang Tian Industrial Square
Suzhou Industrial Park, China 215021
Tel.: +86 512 6283 8870
Fax: +86 512 6283 8890
E-Mail: infohrcn@synventive.com