

MARLINE

Product Specification Marline Premium 2 Temps

Valid from: 2022-03-12

| Parameter | Unit | Requirement | Method |
|--------------------------------|-------------------|----------------|---------------------------------|
| Appearance | - | Clear & Bright | Visual Inspection |
| RON | - | ≥ 93.0 | EN ISO 5164 |
| MON | - | ≥ 90.0 | EN ISO 5163 |
| Density at 15 °C | kg/m ³ | 680 – 720 | EN ISO 12185 |
| DVPE at 37.8 °C | kPa | 55.0 – 65.0 | EN 13016-1 |
| Olefin content | % vol | < 1.0 | EN 15553 |
| Aromatic content | % vol | < 1.0 | SS 155120 Eq. to ASTM D 5443 |
| Benzene content | % vol | < 0.08 | EN 238 |
| Cyclohexane (up to C8) | % vol | < 2.0 | ASTM D 5134 |
| Normalhexane | % vol | < 0.5 | ASTM D 5134 |
| Manganese | mg/L | ≤ 2.0 | EN 16136 |
| Sulphur | mg/kg | ≤ 10.0 | EN ISO 20846 |
| Lead | mg/L | ≤ 2.0 | EN 237 |
| Evaporated at 70 °C | % vol | 15.0 - 42.0 | EN ISO 3405 |
| Evaporated at 150 °C | % vol | ≥ 75.0 | EN ISO 3405 |
| Temperature at 50 % evaporated | °C | 90 – 105 | EN ISO 3405 |
| FBP | °C | ≤ 200 | EN ISO 3405 |
| Distillation residue | % vol | < 3.0 | EN ISO 3405 |
| Oil content | % vol | 1.5 - 2.0 | |
| Copper corrosion 3h at 50 °C | Acc. to scale | Class 1 | EN ISO 2160 |

Marline

ZA Sud Essor

5, rue Marcel Laloyeau

91150 Brières Les Scellés

Tel +33(0)1 69 92 90 99

Fax +33(0)1 60 80 15 58

Mail: info@marline.fr