



INSTALLING
RELIABILITY



www.ndsatcom.com



SKYWAN 5G OUTDOOR

In varied situations – from rough environments to when deployable antenna systems or a tower installation are needed – the SKYWAN 5G Outdoor is the modem of choice. It incorporates the full feature set of the indoor rack 1U SKYWAN 5G VSAT satellite router and is encapsulated in a tough IP65 chassis. The Outdoor version uses the identical software and is controlled the same way as the indoor units. The embedded MF-TDMA and DVB-S2 modem, with its QoS enhanced IP Router with VRF (Virtual Routing and Forwarding) capabilities, is managed by an NMS (Network Management System). The SKYWAN 5G Outdoor supports cascading or N+M redundancy and an internal encryption board with AES-256 if required.

APPLICATIONS

- Cellular Backhaul/Mesh Interconnection of Cells
- Air Traffic Control Networks
- Energy Sector, Oil & Gas
- Access for rural Wireless/Cellular Networks
- Disaster Recovery & Emergency Response
- Closed Enterprise Networks
- Governmental & Administration Networks
- Defence
- Broadcast/Satcom-on-the-Move

YOUR 5G HIGHLIGHTS

- Get all-in-one – the reliable ONE solution
- Gain flexible topology – star to mesh networks
- Gain space & portability – smallest unit available
- Gain powerful performance – with easy interface
- Generate savings – lower cost of ownership

KEY FEATURES

- Built for deployable terminals and cellular network installation
- Robust IP65 chassis
- COTM support with Doppler Shift compensation and COTM antenna interface
- Display and joystick for local set-up
- External AC power supply
- Options for external cooling and weather/sun protection



TECHNICAL SPECIFICATIONS

SKYWAN 5G OUTDOOR (SINCE V1.6.138)

VSAT NETWORK

Network Topology	Star/Hybrid/True Full Mesh, Multi-Master: fully-redundant network control function with seamless switchover	
Supported Satellites/ Transponders	Geostationary, transparent bent-pipes, cross-strapped transponders, HTS spot beams, meshed over HTS spot beams	
Type & Number of Modems	1x MF-TDMA modulator, 1x TDMA demodulator, 1x DVB-S2 receiver (ETSI)	
Access Type TDMA	MF-TDMA with fast frequency hopping in Tx (16 channel) and fixed Rx home channel, pure data channels, Beam Switching, Communication-On-The-Move (COTM) with Doppler shift compensation. Bandwidth-on-Demand DAMA/real-time/non-real-time/guaranteed throughput/QoS classes TDMA Adaptive Coding and Modulation ¹ (ACM) for QPSK up to 16APSK	
Access Type TDM/DVB-S2	DVB-S2 receiver with Adaptive Coding and Modulation (ACM)/MPE and ULE	
Stacking	Cascading of multiple units to one stack for up to 4 TDMA demodulators	
Modulation & FEC Code Rates	TDMA (Turbo-ϕ)	TDM – DVB-S2(X)
	BPSK: 1/3, 2/5, 4/9, 1/2, 2/3	QPSK: 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
	QPSK: 1/3, 2/5, 4/9, 1/2, 2/3, 3/4, 4/5, 5/6, 6/7	8PSK: 3/5, 2/3, 3/4, 5/6, 8/9, 9/10
	8PSK: 2/3, 3/4, 4/5, 5/6, 6/7	16APSK: 2/3, 3/4, 4/5, 5/6, 8/9, 9/10
	16APSK: 2/3, 3/4, 4/5, 5/6, 6/7	32APSK: 3/4, 4/5, 5/6, 8/9, 9/10
Eb/No (BER 10 ⁻⁷ , incl. 0.5 dB margin)	QPSK 1/2: 2.4 dB 8PSK 2/3: 5.8 dB	QPSK 1/2: 1.2 dB 8PSK 9/10: 7.3 dB
Roll-off	16APSK 3/4: 8.2 dB	16APSK 9/10: 8.4 dB 32APSK 4/5: 9.9 dB
Modem Symbol Rate	0.4, 0.2, 0.1	0.35, 0.25, 0.20, 0.15, 0.10, 0.05
User Data Rate	200 ksps – 12 Msps, variable in 1 ksps increments	Up to 45 Msps, variable in 1 sps increments
VSAT Data Throughput	Up to 20 Mbps per Tx or Rx unit, carrier user data rate starting at ~64 kbps, slot assigned traffic starting at ~4 kbps	Up to 80 Mbps unicast/60 Mbps multicast user data rate on LAN port, starting at 3 kbps

BASEBAND INTERFACES

LAN Interface	Four GbE RJ-45 ports, VLAN/VRF/GRE/Jumbo Frames (max 1,600 Byte) configurable per port, local switching
IP Features	IPv4/IPv6 (tunnel)/Static Routing/OSPF/BGP/Multi VRF support (up to 8) including Virtual Channel Groups (VCGr ²) and VLAN/GRE/Multicast Forwarding/IGMPv2/IGMPv3/DiffServ/Class Selector/DSCP/OpenAMIP ³ /DHCP Server
Traffic Processing	Load Balancing/Header Compression/Traffic Filtering with real-time flow detection and Shaping for QoS based on configurable PHB rules (up to 14 classes per VRF) Option: Encryption (AES-256) based on plugin board
Serial RS232/Console	SUB DB-9S socket for management access via command line interface
Aux-Port	8 pin connector DIN 45326 – contains Rx lock signal (5 V DC) indicator and Tx inhibit with cable detect support
Display and 5-button switch	Notification of status information (reception level, IP-address etc.)
USB-A 2.0 ports	1x front panel port for image updates and configuration uploads

RF INTERFACES

Tx Modulator Port	N-connector (50 Ohm female) L-Band 950 – 2150 MHz/-3 ... -43 dBm
Rx Demodulator Port	N-connector (50 Ohm female) L-Band 950 – 2150 MHz/0 ... -70 dBm common used Rx port for DVB-S2 and TDMA receiver
10 MHz reference signal	Configurable by software on Tx and Rx port
Frequency Step Size	Tx and Rx center frequency configurable in 100 Hz steps
LNB	Software configurable 0/13/18 V DC support, 22 kHz signal – internal/external PLL

¹ 6dB range, 18 dB range with HW revision \geq A5
Anticipated release of ACM sw support: First half of 2020

² Patent EP 2871895 A1

³ facilitating data exchange with compliant antenna control units (ACUs)



TECHNICAL SPECIFICATIONS
SKYWAN 5G OUTDOOR (SINCE V1.6.138)

BUC	Software enabled internal 24 V DC support, up to 85 W on IDU N-connector (typical 6 – 8 W Ku)
Others	Radios with L-Band interface – Ka, Ku, Ext Ku, C, X
Shared Amplifier	Multiple SKYWAN 5G modulators can be operated in a multi-carrier setup utilizing the same RF-transmitter without requiring a back-off. Depending on the configured mode, traffic is routed through a single SKYWAN 5G unit or all transmitters are scheduled in sequence to prevent parallel transmission.

10 MHZ REFERENCE SIGNAL SPECIFICATION

Nominal Frequency	10 MHz; frequency tolerance $\leq \pm 2 \times 10^{-7}$ (60 minutes after power on)		
Power Level	Tx: typ. +4 dBm (+3 dBm ... +7 dBm, <-40 dBm when switched off)		
	Rx: typ. -1 dBm (-3 dBm ... +1 dBm, <-46 dBm when switched off)		
Frequency Stability	temperature range 0 °C ... +70 °C:	$\pm 25 \times 10^{-9}$	
	versus supply voltage changes Vs ± 5 %:	$\pm 5 \times 10^{-9}$	
	versus load changes 50 Ω ± 10 %:	$\pm 5 \times 10^{-9}$	
Aging	$\pm 1 \times 10^{-9}$ per day	$\pm 1 \times 10^{-7}$ per year	$\pm 6 \times 10^{-7}$ per 10 years
Phase Noise	1 Hz: -85 dBc	10 Hz: -115 dBc	100 Hz: -140 dBc
	1 kHz: -145 dBc	10 kHz: -155 dBc	100 kHz: -155 dBc



Note: For an optimal and reliable system performance use the SKYWAN 5G reference signal to clock the outdoor equipment (BUC/LNB).

REDUNDANCY

Type

1+1 node redundancy, hot standby

N+M node redundancy, hot standby



Interconnection	LAN Ethernet connection with external switch
External Switch Requirement	VLAN (802.1Q) capable switch with high MTBF and redundant power supply
Switchover	Automatic, no operator intervention required. Operational parameters are mirrored to backup unit for seamless switchover.
Failure Detection	Active monitoring of keep alive signals
Stacking	In a network node with stacked units, the backup unit is agnostic for the function it takes over, it can replace either a Node Controller or a Receiver. Up to 4 active units plus up to 4 backup units form the N+M redundant node.
Operator Support	NMS integrated configuration and monitoring, status display in NMS and SKYWAN 5G front panel

NETWORK MANAGEMENT

Security Architecture	Secure logins (https), role based views/LDAP support, all management interfaces via ssh only
NMS Platform	SKYWAN 5G NMS – virtual appliance optional: pre-installed on NMS server machine
NMS Architecture	Web based application/identical GUI look and feel on NMS and IDU reduces training to a minimum/ central NMS server, can be placed everywhere (only IP connectivity needed) mainly for planning & configuration, network runs without NMS always on or connected, NMS Redundancy, NETCONF (RFC 6241)
IDU Management Interfaces	Remote access with in-band management (from central NMS station over satellite), additional SNMP access for monitoring, local access via WEB-GUI and CLI or integrated console port (RS 232), NETCONF (RFC 6241)
Multi-Language Support	Multi-Language WebUI for NMS and modem, all text can be translated and customized by the operator with the SKYWAN 5G Translation Editor.

TECHNICAL SPECIFICATIONS

SKYWAN 5G OUTDOOR (SINCE V1.6.138)

MECHANICAL/ENVIRONMENTAL

Unit

SKYWAN 5G Outdoor

SKYWAN 5G Outdoor Enclosure



Dimensions (H x W x D)	80 mm x 440 mm x 250 mm	450 mm x 486 mm x 100 mm
Weight	6.5 kg (including external power supply, DVB-S2 receiver card and optional encryption card)	
Mounting Options	indoor, outdoor, mast, in Outdoor Enclosure (additional protection for mechanical action, environmental impact, solar radiation, unauthorized access)	
Input Power/Power Consumption	24 V DC, 40 VA nominal (without BUC/LNB), Binder M12-A Serien 713 Power (4 pins, waterproof, screw lock)	
External Power Supply	Mean Well HEP-150-24 A: Input 100 – 260 V AC, 1.7 A, 50/60 Hz, Output 24 V DC, 6.3 A	
Operating Temperature/Humidity	-20 °C to +55 °C, 5 % – 95 % non-condensing -40 °C to +55 °C, 5 % – 95 % non-condensing with Outdoor Enclosure and heater	
Storage Temperature/Humidity	-40 °C ... +70 °C, 5 % – 95 % non-condensing	
Altitude	Up to 5,000 m above sea level	
International Protection Marking	IP65 for base unit and power supply/IP55 for fans mounted at outside of base unit	
Regulatory Approvals	Fully CE compliant with RoHS and REACH, no export limitations for product	



HEADQUARTERS

ND SatCom GmbH
Graf-von-Soden-Strasse
88090 Immenstaad
Germany
PHONE: + 49 7545 939 0
FAX: + 49 7545 939 8780
E-Mail: info@ndsatcom.com

CHINA

ND SatCom (Beijing) Co. Ltd.
PHONE: +86 10 6590 6869/6878

MIDDLE EAST

ND SatCom FZE
PHONE: +971 4886 5012

WEST AFRICA

ND SatCom Senegal
PHONE: +221 77 569 8017