



**Our vehicles are highly modular, allowing to quickly change vehicle interiors, to suit different types of combat operations, including, but not limited to the following:**

Troop Carrier; Ambulance; Command Vehicle; Specialised Systems Platform.

We are proud to offer a simplified logistics and supply chain, with constant spare parts availability.



---

**INKAS® GEEBOR-II MRAP**

---

WWW.INKASARMORED.COM | +1 416 645 8725 | 3605 WESTON ROAD, TORONTO, ON, M9L 1V7

---



# INKAS® GEEBOR-II MRAP

## Powertrain

Engine	6 cyl, turbo, water-cooled Mechanical or Electronic
Max Power	300-336 kW (403-450 hp)
Max Torque	1,849-1,978 Nm @ 1,200 rpm
Transmission	6-speed automatic
Transfer Case	2-speed all-wheel drive, with locking 4-wheel drive

## Axles/Suspension

Front Axle	Independent Suspension
Axle Rating	10,500 kg (23,100 lb)
Rear Axle	Independent Suspension
Axle Rating	11,500 kg (25,300 lb)
Brake	Disc Brakes. Air operated with optional ABS
Tyres	395/85R20
CTIS	Standard

## Data

Length	6,680 mm (262 in)
Width	2,634 mm (103 in)
Height	2,882 mm (113 in)
Weight GVWR	22,400 kg (49,280 lb)
Empty Weight	15,000 kg (33,000 lb)
Payload	7,400 kg (16,280 lb)
Power/Weight	26.8-30 hp/t (20-22.7 kW/t)

## Crew Capsule

Crew	2+8
Seats	Front: Air cushioned, 4-point harness Rear: Inward facing blast seats, 4-point harness
Emergency Exit	Roof-Mounted Escape Hatch
Cooling	Dual System AC

## Protection

Blast Protection	STANAG 4a, 4b
Ballistic Protection	B7 (Scalable) AEP55 STANAG 3- (7.62x54API; 0.50 cal)

## Performance

Max Road Speed	110 kph (68 mph)
Turning Circle	14.2 m (46.5 ft)
Turning Radius	7.1 m (23 ft)
Gradeability	70%
Approach Angle	31°
Departure Angle	34°
Side Slope	30°
Vertical Obstacle	500 mm (19.68 in)
Ground Clearance	410 mm (16.92 in)
Fording	1.2 m (47.24 in)
Operational Range	600 km (375 mi)