



The Geebor-X Armored Wrecker is the latest product in INKAS® highly successful Geebor MRAP line. The Geebor-X Wrecker offers an 11.3T crane, a 9T drag winch, and a 34T heavy-duty underlift carrier when fully retracted. The focus point of the Geebor-X Wrecker's design is the protection of its crew. With a STANAG

4a/4a blast rating and a B7 all-around ballistic protection AEP55 STANAG 3-, the Geebor-X Wrecker can quickly and safely recover vehicles and stranded troops in the world's harshest terrains and battlefields.

**GEEBOR**



**INKAS® GEEBOR-X WRECKER MRAP**

WWW.INKASARMORED.COM | +1 416 645 8725 | 3605 WESTON ROAD, TORONTO, ON, M9L 1V7



# INKAS® GEEBOR-X WRECKER MRAP

## Powertrain

Engine*	6 cyl, turbo, water-cooled Mechanical or Electronic
Max Power*	300-336 kW (403-450 hp)
Max Torque*	1,849-1,978 Nm @ 1,200 rpm
Transmission	6-speed automatic
Transfer Case	2-speed all-wheel drive, with lockable 4-wheel drive

## Weights/Dimensions

GVW	31,000 kg (68,343 lb)
Wheel Config	6x6
Frame	315 mm x 75 mm x 8 mm (12.4 in x 2.95 in x 0.31 in) Reinforced Chassis
Wheelbase	6,200 mm (244.09 in)
Platform	3,980 mm (156.69 in)
Overhang	883 mm (34.76 in)
Ground Clearance	380 mm (14.96 in)
Fuel Capacity	280 L
Operational Range	600-650 km Range

## Crane

Boom Rating	11,339 kg (24,998 lb)
Hook Height	6,500 mm (255.91 in)
Boom Extension	3,048 kg (6,719 lb)
Boom Winch	13,607 kg (29,998 lb)

## Drag Winch

Winch Capacity	9,071 kg (19,998 lb)
Winch Type	Dual Planetary 2-speed
Cable	14.3 mm x 145 m

\* Choice of Deutz or Caterpillar powerpack

Specifications may be subject to change.

## Underlift

Extended Lift	5,896 kg @ 2,489 mm
Retracted Lift	11,339 kg @ 1,422 mm
Tilt Arc	30°
Towing Rating	34,019 kg (74,999 lb)

## Axles/Suspension

Front Axle	Independent Suspension
Axle Rating	10,435 kg (23,005 lb)
Rear Axles (x2)	Independent Suspension
Axle Rating	11,339 kg (24,998 lb)

## Crew Capsule/Chassis

Crew Capsule	Driver + 1
Seats	Air suspended with 4-point harness
Emergency	Roof-Mounted Escape Hatch
Cooling	AC 5 kW in Cab Observation
Observation	Monitoring screen in cab with two rear-mounted cameras covering rear and load

## Protection

Blast	STANAG 4a/4b
Ballistic	B7 AEP55 STANAG 3- (7.62 x 54API; 0.50 cal)
Hatch Mount	Upon Request

The Geebor-X Armored Wrecker follows on with the Geebor core principles: simple robust mechanical systems; ease of maintenance; crew safety; and austere environment dependability.