

# **CLARK MASTS™ FT-RM Series**

***Lightweight, telescopic masts with attached tripod for directional or omni-directional headloads***

FT masts are typically field masts derived from the well-known QT mast range.

Easy and quick to deploy, manually or with handpump and supported with three foldable legs which are permanently attached to the mast.



***CLARK MASTS - Pioneer in fast erecting mast systems***



# Technical Details

*Silent, smooth and easy operation*



PHOTO SHOWS SFT-RM4-4/H MAST (MANUALLY EXTENDED)

**The features that have made it such an attractive and useful piece of equipment are :**

1. Aluminium alloy sections
2. Handpump (not for manually extended masts)
3. Field base
4. Leg clamp
5. Air-release screw (not for manually extended masts)
6. Section-clamping screws
7. Guy collar
8. Turning Collar
9. Quick-clamp for headload



PHOTO SHOWS SFT-RM4-4/HP MAST

# Standard FT-RM Mast Range

*Manually extended or with handpump*

## Rotatable FT-RM Mast Range (extended with handpump)

3" / 76,2mm BASE TUBE

Mast Model	Cat. No.	Retracted Height	Extended Height	Standard Finish	Max. Headload	Mast Guying Kit Cat. No.
<b>3 section masts</b>						
SFT-RM3-3/HP	27992	1,48 m	3,30 m	nato green	20,0 kg	33720-NG
<b>4 section masts</b>						
SFT-RM4-4/HP	33000	1,54 m	4,20 m	nato green	20,0 kg	33721-NG
<b>5 section masts</b>						
SFT-RM5-5/HP	33004	1,55 m	5,10 m	nato green	15,0 kg	33722-NG
<b>6 section masts</b>						
SFT-RM6-6/HP	33008	1,58 m	6,05 m	nato green	10,0 kg	33723-NG
SFT-RM9-6/HP	33020	2,07 m	8,80 m	nato green	10,0 kg	33726-NG
SFT-RM10-6/HP	33024	2,33 m	10,05 m	nato green	10,0 kg	33727-NG
<b>7 section masts</b>						
SFT-RM7-7/HP	33012	1,62 m	7,00 m	nato green	6,0 kg	33724-NG
SFT-RM11-7/HP	33028	2,29 m	11,05 m	nato green	4,5 kg	33728-NG
<b>8 section masts</b>						
SFT-RM8-8/HP	33016	1,65 m	7,95 m	nato green	4,5 kg	33725-NG
SFT-RM12-8/HP	33032	2,13 m	11,60 m	nato green	2,5 kg	33729-NG

## Rotatable FT-RM Mast Range (manually extended)

3" / 76,2mm BASE TUBE

Mast Model	Cat. No.	Retracted Height	Extended Height	Standard Finish	Max. Headload	Mast Guying Kit Cat. No.
<b>3 section masts</b>						
SFT-RM3-3/H	33072	1,44 m	3,05 m	nato green	10,0 kg	33720-NG
<b>4 section masts</b>						
SFT-RM4-4/H	33074	1,47 m	4,05 m	nato green	10,0 kg	33721-NG
<b>5 section masts</b>						
SFT-RM5-5/H	33076	1,50 m	5,05 m	nato green	10,0 kg	33722-NG
<b>6 section masts</b>						
SFT-RM6-6/H	33078	1,53 m	6,00 m	nato green	10,0 kg	33723-NG



# FT-RM Masts Mounting Accessories

## FT-RM Mast Guying Kits

For all FT-RM Series masts is a Mast Guying Kit available consisting of Spikes, Canvas Top Cover, Pickets, Hammer, Radius Line, Top guys + Middle Guys (if applicable) and Accessory Bag.



PHOTO SHOWS "FT-RM KIT" VERSION WITH OPTIONAL MAST CARRYING BAG

## FT-RM Mast Carrying Bags

The FT-RM Series masts are also available with an optional carrying bag to simplify transport or just for protection of the stored mast.

### FT-RM Mast Carrying Bags for rotatable masts (extended with handpump)

Mast Carrying Bags internal length	Cat. No.
1500 mm	30221-NG
1550 mm	30222-NG
1600 mm	30223-NG
1700 mm	30224-NG
2100 mm	30225-NG
2160 mm	30226-NG
2400 mm	30228-NG

### FT-RM Mast Carrying Bags for rotatable masts (manually extended)

Mast Carrying Bags internal length	Cat. No.
1450 mm	30220-NG
1500 mm	30221-NG
1550 mm	30222-NG

# CLARK MASTS™

All details given in this publication are approximate and may be subject to change without notice.

Distributor :

**TEKSAM COMPANY NV**, Woudstraat 21, 3600 Genk, Belgium

Tel : +32 (0)89 38 44 72 Fax : +32 (0)89 38 61 41 E-mail : [info@teksamco.com](mailto:info@teksamco.com) Website : [www.clarkmasts.be](http://www.clarkmasts.be)