

Technical Data Automatic components

PAH-1



- Universal design for flat surfaces
- Hand gun for fully automatic stud feed (with VBZ-3) or hand feed
- Recommended for large-scale production

M3 to M8 #4 to 5/16'





- Used for welding with templates
- Hand gun for fully automatic stud feed (with VBZ-3) or hand feed
- Recommended for large-scale production

M3 to M8 #4 to 5/16'



Suitable stud welding unit	CDi 1502, CDMi 2402, CDMi 3202, ARC 800, IT 1002, IT 90	CDi 1502, CDMi 2402, CDMi 3202, ARC 800, IT 1002, IT 90
Welding process	CD, SC	CD, SC
Stud material	• • • •	• • • •
Welding range	M3 to M8, dia. 3 to 8 mm / #4 to 5/16", dia. #4 to 5/16"	M3 to M8, dia. 3 to 8 mm / #4 to 5/16", dia. #4 to 5/16"
Stud length	8 to 30 mm / 0.31" to 1.18"	8 to 30 mm / 0.31" to 1.18"
Stud type	Welding elements with flange according to current standards (other studs on request)	Welding elements with flange according to current standards (other studs on request)
Lift	Adjustment range 5 mm / 0.20"	Adjustment range 5 mm / 0.20"
Welding cable	3 m / 9.84'	3 m / 9.84'
IP Code	IP 20	IP 20
Workplace noise level	> 90 dB (A) may occur during welding	> 90 dB (A) may occur during welding
Dimension LxWxH	295 x 60 x 170 mm / 11.61" x 2.36" x 6.70" (without cable)	295 x 60 x 170 mm / 11.61" x 2.36" x 6.70" (without cable)
Weight	1.4 kg / 3.09 lbs (without cable)	1.4 kg / 3.09 lbs (without cable)

Order No.

94-20-025 (Tripod)

Equipped for one standard stud dimension according to customer request (possible equipment see accessories catalogue page 86 - 93)

Sets

CDi1504PAH+ (CDi 1502, PAH-1, ground cable) (CDMi 2402, PAH-1, ground cable) CDMi242AT+ (ARC 800, PAH-1, ground cable) ARC8001AT+

Assortment box

(Pin stop, guide bushing, mounting tool, feed tube, socket wrench, plunger, pin)

84-40-013A (dia. 3 to 8 mm, length 6 to 30 mm, for manual stud feeding by hand) 84-43-013A (dia. 3 to 8 mm, length 6 to 30 mm, for automatic stud feeding by VBZ-3)

Quick-Boy

92-40-140 for PAH-1

Order No.

94-20-028 (centering device dia. 30 mm) Equipped for one standard stud dimension according to customer request (possible equipment see accessories catalogue page 86 - 93)

Assortment box

(Pin stop, guide bushing, mounting tool, feed tube, socket wrench, plunger, pin)

84-40-013A (dia. 3 to 8 mm, length 6 to 30 mm, for manual stud feeding by hand) 84-43-013A (dia. 3 to 8 mm, length 6 to 30 mm, for automatic stud feeding by VBZ-3)

Quick-Boy

92-40-140 for PAH-1

Welding process: CD = Capacitor discharge stud welding, SC = Short cycle stud welding









