

BLOWER HEATED TYPE ADSORPTION DRYERS



-40°C / -70°C
DEW POINT



OPTIONAL DEW POINT
CONTROLLED
PRODUCTION



DOKUNMATİK EKLANLI
PLC KONTROL SİSTEMİ



MAX 2% AIR LOSS



ECONOMICAL DRY
AIR GENERATION

AKDAB
AKDAC
SERIES



2% Air Loss, PDP = -40°C / -70°C



TECHNICAL DATA

Model	Pressure Dew Point		FAD 7 Bar(g) 100 Psig			Connection Size	Voltage	Dimensions		
	AKDAB	AKDAC	lt/min	m ³ /h	cfm			Height (mm)	Width (mm)	Depth (mm)
6001	-40	-70	6000	360	212	1½"	230V / 1 Ph / 50 Hz	1750	800	1250
9001	-40	-70	9000	540	318	1½"	230V / 1 Ph / 50 Hz	1800	900	1400
12001	-40	-70	12000	720	424	2"	230V / 1 Ph / 50 Hz	1850	1000	1500
16001	-40	-70	16000	960	565	2"	380V / 3 Ph / 50 Hz	1900	1000	1500
20001	-40	-70	20000	1200	707	DN 80	380V / 3 Ph / 50 Hz	2580	1200	1800
25001	-40	-70	25000	1500	883	DN 80	380V / 3 Ph / 50 Hz	2600	1200	1800
30001	-40	-70	30000	1800	1060	DN 80	380V / 3 Ph / 50 Hz	2700	1300	2400
40001	-40	-70	40000	2400	1412	DN 100	380V / 3 Ph / 50 Hz	2950	1350	2500
50001	-40	-70	50000	3000	1766	DN 100	380V / 3 Ph / 50 Hz	2950	1450	2600
75001	-40	-70	75000	4500	2649	DN 125	380V / 3 Ph / 50 Hz	2950	1550	2750
95001	-40	-70	95000	5700	3355	DN 150	380V / 3 Ph / 50 Hz	2950	2200	3000
120001	-40	-70	120000	7200	4238	DN 150	380V / 3 Ph / 50 Hz	2950	2200	3200
160001	-40	-70	160000	9600	5660	DN 150	380V / 3 Ph / 50 Hz	2950	2500	3400

OUR COMPANY MAY CHANGE THE VALUES IN THE CATALOGUE ACCORDING TO THE RESEARCH AND DEVELOPMENT STUDIES.