

Q-TOOL

AUTO-Q

Automatic Rivet Feeding System

NEW



Boost your production efficiency with our state-of-the-art **Automatic Rivet Feeding System**, designed to streamline the riveting process across various industrial applications.

- › **High-Speed Operation:** Feeds up to 60 rivets per minute, optimizing throughput and significantly reducing assembly times.
- › **User-Friendly Design:** Features a simple and robust structure for easy maintenance, ensuring long-term reliability in demanding production environments.
- › **Fully Automated Process:** Eliminates manual rivet picking and placement, drastically improving operational speed and precision.

Versatile Compatibility: Accommodates rivets ranging from Ø 3.2 mm to Ø 4.8 mm, making it adaptable to a wide range of applications.

This advanced system enhances productivity, minimizes downtime, and delivers consistent, high-quality riveting performance for your production line.

QONNECT

AUTO-Q R32, R40 & R48



Technical Specifications

Type	R32	R40	R48
Loading Capacity	2.400 pcs	1.500 pcs	1.000 pcs
Rivet Diameter	3.2 mm	4.0 mm	4.8 mm
Stroke	18 mm	18 mm	20 mm
Force	5 - 7 kN	8 - 12 kN	11 - 15 kN
Feeding Speed	60 pcs/min		
Feeding Tube	2.3 m		
Air Pressure	5.0 - 7.0 bar		
Power Supply	100 ~ 240 Vac, 50/60 Hz		
Machine Size	503 × 385 × 395 mm		
Net Weight	45 kg		

